

Specifications Table for FTXA-CW

				FTXA20C2V1BW	FTXA25C2V1BW	FTXA35C2V1BW	FTXA42C2V1BW	FTXA50C2V1BW		
Power input	Cooling	Nom.	kW	0.020	0.022	0.023	0.028	0.030		
	Heating	Nom.	kW	0.020	0.020	0.220	0.036	0.039		
Casing	Colour			White	White	White	White	White		
Dimensions	Unit	Height	mm	295	295	295	295	295		
		Width	mm	798	798	798	798	798		
		Depth	mm	189	189	189	189	189		
Weight	Unit		kg	11.5	11.5	11.5	11.5	11.5		
Fan	Air flow rate	Cooling	High	m ³ /min	11.0	11.5	11.9	13.1	13.5	
			Medium	m ³ /min	8.2	8.6	8.6	9.8	10.4	
			Low	m ³ /min	6.1	6.1	6.1	7.2	7.6	
			Silent operation	m ³ /min	4.6	4.6	4.6	4.6	5.2	
	Heating	High	m ³ /min	10.9	11.1	11.5	14.6	15.1		
		Medium	m ³ /min	8.7	9.0	9.0	10.5	11.1		
		Low	m ³ /min	6.4	6.4	6.4	7.7	8.2		
		Silent operation	m ³ /min	4.5	4.5	4.5	5.2	5.7		
		Sound power level	Cooling		dBA	57	57	60	60	60
		Sound pressure level	Cooling	High	dBA	39	40	41	45	46
Medium	dBA			32	33	33	37	39		
Low	dBA			25	25	25	29	31		
Silent operation	dBA			19	19	19	21	24		
Heating	High		dBA	39	40	41	45	46		
	Medium		dBA	32	33	33	37	42		
	Low		dBA	25	25	25	29	33		
	Silent operation		dBA	19	19	19	21	24		
	Refrigerant		GWP			675.0	675.0	675.0	675.0	675.0
	Piping connections		Liquid	OD	mm	6.35	6.35	6.35	6.35	6.35
Gas		OD	mm	9.50	9.50	9.50	9.50	12.70		

	Drain		18	18	18	18	18
Control systems	Infrared remote control		ARC466A85	ARC466A85	ARC466A85	ARC466A85	ARC466A85
	Wired remote control		BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1
Standard Accessories	Installation manual		1	1	1	1	1
	Operation manual		1	1	1	1	1
	Air filter		2	2	2	2	2
	Infrared remote control		1	1	1	1	1
	Remote controller mounting plate		1	1	1	1	1
	Screw bag		1	1	1	1	1
	Screw cover		2	2	2	2	2
	AAA dry-cell batteries		2	2	2	2	2
	General safety precautions		1	1	1	1	1
	Power supply	Name		V1	V1	V1	V1
Phase			1~	1~	1~	1~	1~
Frequency		Hz	50	50	50	50	50
Voltage		V	220-240	220-240	220-240	220-240	220-240

^