

Streamer technology air purifier with UK plug

MC30YB



Flash Streamer

Powerful air purification

- › Pure air thanks to Daikin 'Catch and Clean' approach in decomposing harmful substances
- › High performance electrostatic HEPA filter which doesn't clog easily, hence causes low pressure loss

- › One of the most silent Air Purifier range on the European market
- › No need to change the filter for ten years, resulting in low maintenance costs
- › Purifies the air in rooms up to 46m²

MC30YB



Indoor Unit				MC	30YB
Application					Floor standing type
Applicable room area				m²	23 (1) / 46 (2)
CADR				m³/h	180 (3)
Weight	Unit			kg	5.8
Dimensions	(H x W x D)			mm	450 / 270 / 270
Casing	Colour				White
Fan	Type				Multi Blade Fan (Sirocco fan with shroud assembly)
	Air flow rate	Air purifying operation	Silent/Medium/Turbo	m³/h	60 /120 /180
Sound pressure level (4)	Air purifying operation		Silent/Medium/Turbo	dBA	19 /27 /37
Air purifying operation	Power input		Silent/M/Turbo	kW	0.008 /0.015 /0.025
Deodorizing method					Flash streamer + Deodorizing catalyst
Dust collecting method					Electrostatic HEPA filter (5)
Air filter	Type				Polyethylene terephthalate net
Sign	Item	01			Airflow rate: Silent/Standard/Turbo / Child proof lock lamp / ON/OFF lamp / Streamer lamp / Sleep mode
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220-230
Type					Air Purifier

(1) The applicable room area is appropriate for operating the unit of maximum fan speed (HH). Applicable room area indicates the space where a certain amount of dust particles can be removed in 30 minutes. (JEM 1467.)

(2) The applicable room area is appropriate for operating the unit of maximum fan speed (HH). Applicable room area was calculated in accordance with NRCC-5401 standard using cigarette smoke CADR that was tested according to JEM1467.

(3) Converted to CADR standards from test values in accordance with JEM1467.

(4) Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) |

(5) Electrostatic HEPA filter is attached in the unit. |

(6) Other function : Auto-restart function.

