



DEVIdry™ Pro Kit

The DEVIdry™ Pro Kit is used to control the DEVIdry™ floor heating system designed for floor heating in dry rooms under wooden floorings, parquets and laminates.

The kit consists of the DEVIreg™ Touch thermostat, the Circuit Device, the NTC Floor Sensor, the Supply Cord, the Power Supply Cord, the Connection Tool and aluminium Tape.

2
YEAR
WARRANTY



Benefits:

- All-in-the-box
- Easy installation
- Digital timer thermostat
- Low standby consumption
- Childproof function

Standard compliance:

- EN/IEC 60335-2-96 (with DEVIdry™)
- EN/IEC 60730-1 (general)
- EN/IEC 60730-2-9 (thermostat)

| Type | DEVIreg™ Touch |
|--------------------------------|--|
| Operation voltage | 220 - 240 V~ 50/60 Hz |
| Standby power consumption | max. 0,40 W |
| Resistive load | 16A, 3680 W @ 230 V |
| Inductive load | Max. 1 A, cos φ = 0,3 |
| Sensing unit | NTC 15 kΩ @ 25 °C |
| Ambient temperature | 0 °C to 30 °C |
| Frost protection | 5°C to 9°C (default 5°C) |
| Temperature range | 5 °C to 35°C (room) 5 °C to 45 °C (floor) |
| Cable specification max | 1 x 4 mm ² or 2 x 2,5 mm ² |
| Ball pressure test temperature | 75 °C |
| Pollution degree | 2 (domestic use) |
| Controller type | 1 C |
| Storage temperature | -20°C to +65°C |
| IP class | 21 |
| Protection class | Class II - <input type="checkbox"/> |
| Dimensions (H/W/D) | 85 x 85 x 20-24 mm (in-wall depth: 22 mm) |
| Weight | 115 g |

Types

| Item no. | Product name | Type | EAN no. |
|----------|------------------|---------------------|---------------|
| 19911006 | DEVIdry™ Pro Kit | With DEVIreg™ Touch | 5703466194515 |

Accessories

| Item no. | Product name | Type | EAN no. |
|----------|--------------|------------------------------------|---------------|
| 19911009 | Supply cord | 3 m, 1 mm ² , max. 10 A | 5703466197301 |

| Output | Subfloor | | Top floor | |
|----------------------|----------|----------|-----------|----------|
| | Wood | Concrete | Wood | Laminate |
| 55 W/m ² | + | + | + | + |
| 100 W/m ² | - | + | + | + |