


Tehnički list za artikl: H5ULG02K0G

Prespojni kabel RJ45 cat.5e neoklopljen, PVC, sivi, 2.0m



SCHRACK info

Prespojni kabeli za primjenu u komunikacijskim sustavima. Podržava standarde klase D (npr. 1000Base-T, 100Base-TX, ATM) kao i VoIP, PoE.

Prespojni kabeli se isporučuju s plastičnim brizganim pregibnicama u istoj boji kao i sam kabel. Raspored pinova 1:1.



Tehnički podaci

Neto duljina (mm)	20,00
Neto širina (mm)	190,00
Neto visina (mm)	170,00
Neto masa (kg)	0,08
Bit rate	up to Gigabit Ethernet
Kategorija	Cat.5e
Cable construction	4x2xAWG24/7
Kabelski oklop	U/UTP
Vanjski omotač kabela	PVC
Connection	1:1

Tehnički podaci - nastavak

Broj parica	4
Oklop	Neoklopljen
LED funkcija	bez LED
Boja	siva
Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	60
RoHS	conform
Connector standard	EN 60603-7
Connector type	RJ45 unshielded
Pin assignment	EIA/TIA 568B 1:1
Pakiranje	Single packed in polybag with label
Duljina prespojnog kabela (m)	2,0

Tablica artikla

OPIS	NVP (%)	MASA BAKRA (kg/km)	KAT. BROJ
Prespojni kabel RJ45 cat.5e neoklopljen, PVC, sivi, 2.0m			H5ULG02K0G
Dodatni pribor			
TOOLLESS LINE utični modul RJ45 cat.5e, neoklopljen (SFA)			HSEMRJ5UWS
Prespojni panel 24xRJ45 cat.5e, neoklopljen, 19", 1U, RAL7035 svijetlo siva			HSERU245GF
Priključnica 2xRJ45 cat.5e, neoklopljena, 80x80, RAL9010			HSEDU2UW5F
U/UTP inst. kabel cat.5e, 4x2xAWG24/1, PVC,Eca,plavi,305m	69	15	HSEKU424P1
U/UTP inst. kabel cat.5e,4x2xAWG24/1,PVC,Eca,sivi,305m	69	15	HSEKU424P0
U/UTP inst. kabel cat.5e,4x2xAWG24/1,LS0H,Eca,plavi,305m	69	15	HSEKU424H1