


Geberit Silent-PP koljeno



Ogledna slika



Namjeravana uporaba

- Za odvodnju otpadne vode unutar zgrada
- Za sustave centralnog usisavanja u jednoobiteljskim kućama primijeniti isključivo koljena 45° dimenzija DN 40–50
- Za tlačne vodove pumpi za otpadnu vodu prema EN 12050-2 i EN 12050-3 koristiti isključivo dimenzije DN 32–50

- Brtva od EPDM-a

Tehnički podaci

Temperatura kod montaže	-10 – +40 °C
Materijal	PP-MD
Toplinsko rastezanje	0.08 mm/(m·K)

Svojstva

- Zvučno optimirano

Art. br.	DN	d, ø	arc	X	Z	Z1
390.020.14.1	30	32 mm	15°	5 cm	0.6 cm	1 cm
390.120.14.1	40	40 mm	15°	5.4 cm	0.7 cm	1.1 cm
390.220.14.1	50	50 mm	15°	5.8 cm	0.7 cm	1.1 cm
390.320.14.1	70	75 mm	15°	6.5 cm	0.9 cm	1.5 cm
390.420.14.1	90	90 mm	15°	7.3 cm	1.2 cm	1.7 cm
390.520.14.1	100	110 mm	15°	8.2 cm	1.4 cm	2 cm
390.620.14.1	125	125 mm	15°	8.8 cm	1.4 cm	2.3 cm
390.720.14.1	150	160 mm	15°	9.7 cm	1.7 cm	2.6 cm
390.021.14.1	30	32 mm	30°	5.2 cm	0.8 cm	0.9 cm
390.121.14.1	40	40 mm	30°	5.7 cm	0.9 cm	1 cm
390.221.14.1	50	50 mm	30°	6.2 cm	1.1 cm	1 cm
390.321.14.1	70	75 mm	30°	7 cm	1.5 cm	1.5 cm
390.421.14.1	90	90 mm	30°	7.9 cm	1.8 cm	1.7 cm
390.521.14.1	100	110 mm	30°	9 cm	2.1 cm	2.2 cm
390.621.14.1	125	125 mm	30°	9.8 cm	2.4 cm	2.5 cm
390.721.14.1	150	160 mm	30°	11 cm	3 cm	2.8 cm
390.022.14.1	30	32 mm	45°	5.5 cm	1 cm	1.1 cm
390.122.14.1	40	40 mm	45°	6 cm	1.2 cm	1.3 cm
390.222.14.1	50	50 mm	45°	6.5 cm	1.5 cm	1.4 cm
390.322.14.1	70	75 mm	45°	7.6 cm	2 cm	2.1 cm
390.422.14.1	90	90 mm	45°	8.5 cm	2.4 cm	2.5 cm
390.522.14.1	100	110 mm	45°	9.7 cm	3 cm	2.9 cm
390.622.14.1	125	125 mm	45°	10.7 cm	3.3 cm	3.3 cm
390.722.14.1	150	160 mm	45°	12.2 cm	4.2 cm	4 cm
390.023.14.1	30	32 mm	67.5°	5.9 cm	1.5 cm	1.5 cm
390.123.14.1	40	40 mm	67.5°	6.5 cm	1.8 cm	1.8 cm
390.223.14.1	50	50 mm	67.5°	7.2 cm	2.1 cm	2.1 cm
390.323.14.1	70	75 mm	67.5°	8.6 cm	3 cm	3 cm
390.423.14.1	90	90 mm	67.5°	9.7 cm	3.6 cm	3.5 cm

Art. br.	DN	d, ø	arc	X	Z	Z1
390.523.14.1	100	110 mm	67.5 °	11.2 cm	4.4 cm	4.3 cm
390.623.14.1	125	125 mm	67.5 °	12.3 cm	4.9 cm	4.9 cm
390.723.14.1	150	160 mm	67.5 °	14.3 cm	6.2 cm	6.1 cm
390.024.14.1	30	32 mm	87.5 °	6.4 cm	1.9 cm	2 cm
390.124.14.1	40	40 mm	87.5 °	7.1 cm	2.3 cm	2.5 cm
390.224.14.1	50	50 mm	87.5 °	7.9 cm	2.8 cm	3 cm
390.324.14.1	70	75 mm	87.5 °	9.7 cm	4.1 cm	4.2 cm
390.424.14.1	90	90 mm	87.5 °	11 cm	4.9 cm	4.8 cm
390.524.14.1	100	110 mm	87.5 °	12.8 cm	6 cm	6 cm
390.624.14.1	125	125 mm	87.5 °	14.2 cm	6.8 cm	6.7 cm
390.724.14.1	150	160 mm	87.5 °	16.6 cm	8.5 cm	8.4 cm